

BLITZTANK

INSTRUCTIONS FOR SELF- SERVICE OUTLETS

(USE GLOVES, APRON & SAFETY GLASSES)

Switch off power and remove plug from power point, then turn the thermostat indicator dial to zero, before commencing the next step !!

1. **Drain Tank** – Remove 1” plastic plug (if supplied) and attach drainage pipe (supplied) into drain cog. Open valve and drain contents of tank including any carbon / debris on the bottom to grease trap via the floor drain. Powersafe detergent is **biodegradable**.
2. **Rinse** inside of tank with clean water, close drain valve, remove drain hose and fitting and re-insert 1” plastic plug (if supplied)
3. **Clean outside** of tank with stainless steel oil cleaner, using a yellow / green Scotch-Brite sponge/scourer and soft cloth to polish.
4. **Fill tank** to required level with clean water (**preferably hot**) as per indication line on inside back of tank.
5. **Switch tank ‘on’** at power point and set thermostat to 80 degrees. (Red light will illuminate to indicate proper operation)
6. **Add** specified amount of Powersafe **detergent** as per Powertank specifications.
7. **Very Important !!** Agitate water and detergent by means of moving the basket up and down, thus dissolving detergent and preventing the formation of lumps.

MAKE SURE YOU PUT THE POWDER INTO THE WATER - NOT THE WATER INTO THE POWDER AS THIS WILL CAUSE A SOLID ROCK TO FORM !!!